

LELAND POWELL - Preliminary Equipment List

COLD HEADERS 2-DIE 3-BLOW

½" Asahi Okuma Model ORH-120 2-Die 3-Blow Cold Header; s/n n/a, 9/16" Cutoff Diameter Mild Steel, 5-1/8" 1st Die Kickout, 3-9/16" 2nd Die Kickout, 4" Cutoff Length, 100 PPM, Equipped with Bushing Cutoff, PKO, RKO, Face of Die Stripper

5/16" National Model 56C 2-Die 3-Blow Convertible Cold Header; s/n 41329 (Build 1984), 3/8" Cutoff Diameter Mild Steel, 5/16" Cutoff Diameter Alloy Steel, 2-1/2" Shank Length, 4-1/4" Cutoff Length, 150 PPM, Equipped with Bushing Cutoff, PKO, Trim, Ace Monitor, Pneumatic Feed Roll Clamps, Convertible Feature

(2) 5/16" National Model 56 2-Die 3-Blow Cold Header; s/n 40867 with PKO and Face of Die Stripper and s/n 40866 with PKO, Face of Die Stripper and Brankamp, 3/8" Cutoff Diameter Mild Steel, 5/16" Cutoff Diameter Alloy Steel, 2-1/2" Shank Length, 4-1/4" Cutoff Length, 150 PPM, Equipped with Bushing Cutoff

5/16" Nakashimada Model NP81 2-Die 3-Blow Cold Header; s/n 000042, 8 MM Cutoff Diameter, 80 MM Shank Length, 100 MM Cutoff Length, 55-160 PPM, Equipped with Bushing Cutoff, Ace Monitor, Wiper, Oil Centrifuge, 2-Plane Straightener

(4) 3/16" National Model 34 2-Die 3-Blow Cold Headers; s/n 41614 with PKO, s/n 41606 with Face of Die Stripper, s/n 41608 with PKO and Face of Die Stripper, s/n 41671 with PKO, Face of Die Stripper, and IAC Enclosure, ¼" Cutoff Diameter Mild Steel, 5/16" Cutoff Diameter Alloy Steel, 1/8" – 2-1/4" Shank Length, 2-1/2" Cutoff Length, 200 PPM, Equipped with Bushing Cutoff

COLD HEADERS 2-DIE 2-BLOW

3/8" Asahi Okuma Model AOT-10B 2-Die 2-Blow Cold Header; s/n 23-180, 10 MM Cutoff Diameter, 75 MM Shank Length, 80 MM Cutoff Length, 20 MM PKO Stroke, 200 PPM, Bushing Cutoff

¼" Asahi Okuma Model AOT6XL Long Stroke 2-Die 2-Blow Cold Header; s/n 4-116, ¼" Cutoff Diameter, 75 MM Shank Length, 95 MM Cutoff Length, 10 MM PKO Stroke, 220 PPM, Busing Cutoff, Face of Die Stripper

¼" Sacma Model SP-22 2-Die 2-Blow Cold Header; s/n 33KP3, 6 MM Cutoff Diameter, 100 MM Shank Length, 110 MM Cutoff Length, 170 PPM, Ace Monitor

5/16" Asahi Okuma Model AOT-8B 2-Die 2-Blow Cold Header; s/n 20196, 8 MM Cutoff Diameter, 55 MM Shank Length, 60 MM Cutoff Length, 15 MM PKO Stroke, 250 PPM, Bushing Cutoff, Face of Die Stripper

LELAND POWELL - Preliminary Equipment List

5/16" Nakashimada Model TH2-8A 2-Die 2-Blow Cold Header; s/n n/a, 8 MM Cutoff Diameter, 50 MM Shank Length, 75 MM Cutoff Length, 25 MM PKO Stroke 1st, 10 MM PKO Stroke 2nd, 250 PPM, Bushing Cutoff, PKO, IFO Transfer, Trimming, Ace Monitor

COLD HEADERS – MISC.

½" National Model 810 DSSD Cold Header; s/n 33773, ½" Cutoff Diameter Alloy, 5/8" Cutoff Diameter Mild Steel, 2-1/2" Shank Length, 4-1/2" Cutoff Length, 120 PPM, Bushing Cutoff, PKO, RKO, Ace Monitor

½" Manville Model 500 DSSD Cold Header; s/n n/a, ½" Cutoff Diameter, 4" Shank Length, 6" Cutoff Length, 50-60 SPM

3/8" Asahi Okuma Model AOS-10 DSSD Cold Header; s/n 9-1018, 10 MM Cutoff Diameter, 70 MM Shank Length, 80 MM Cutoff Length, 180 PPM

3/8" National DSSD Cold Header; s/n 33309, 3/8" Cutoff Diameter, 1-3/4" Shank Length, 3-1/4" Cutoff Length, 100 PPM, Equipped with PKO, Open Cutter

8 MM Sacma Model SP15 4-Die Progressive Cold Header; s/n 58AH180, 8 MM Cutoff Diameter, 60 MM Shank Length, 80 MM Cutoff Length, 200 PPM, Equipped with PKO, IFO Cam, Ace Monitor

(4) 5/16" Sacma Model SP21 DSSD High Speed Cold Header; s/n 37AO17, 37AF141, 37AE144, 37AE150, 5/16" Cutoff Diameter, 3-3/16" Shank Length, 4-1/8" Cutoff Length, 200 PPM, Equipped with Ace Monitors

5/16" National 3-Die Progressive Cold Header; s/n 27163, 5/16" Cutoff Diameter, 3-1/8" Shank Length, 3-3/6" Cutoff Length, 90 PPM, Trimming, Ace Monitor

(8) ¼" Sacma Model SP11 DSSD High Speed Cold Headers; s/n 41AM81, 41AH70, 41AS16, 41XI73, 41WL28, 41AD23, 43AL19, NA, ¼" Cutoff Diameter, 2" Shank Length, 2-3/4" Cutoff Length, 275 PPM, All Equipped with Ace Monitor

¼" Nakashimada Model NS-60 High Speed DSSD Cold Header; s/n 080046, 6 MM Cutoff Diameter, 50 MM Shank Length, 70 MM Cutoff Length, 20 MM PKO Stroke 1st, 5 MM PKO Stroke 2nd, 250 PPM, Bushing Cutoff,

LELAND POWELL - Preliminary Equipment List

¼" National Model 45 High Speed Long Stroke Single Die Tubular Rivet Header; s/n 35703, ¼" Cutoff Diameter, 2" Shank Length, 3" Cutoff Length, ½" Depth Piece, 200 PPM, Equipped with Bushing Cutoff, Face of Die Stripper

¼" National Model 45 High Speed Medium Stroke DSSD Cold Header; s/n 34714, ¼" Cutoff Diameter, 2" Shank Length, 3" Cutoff Length, 300 PPM, Equipped with Bushing Cutoff, PKO, RKO, IAC, Ace Monitor

¼" National High Speed DSSD Cold Header; s/n 32373, ¼" Cutoff Diameter, 1-3/8" Shank Length, 2-3/8" Cutoff Length, 265 PPM, Equipped with Bushing Cutoff, PKO

¼" National 4-Die Progressive Cold Header; s/n 27306, ¼" Cutoff Diameter, 2-1/2" Shank Length, 3-1/4" Cutoff Length, 100 PPM

¼" Chunzu Model CH6LL Long Stroke DSSD Cold Header; s/n 88033-4, ¼" Cutoff Diameter, 4" Shank Length, 5" Cutoff Length, ½" PKO Stroke, 110 PPM, Equipped with Ace Monitor, 2-Plane Straightener

3/16" National High-Speed Single Die Tubular Rivet Header; s/n 36104, 3/16" Cutoff Diameter, ¾" Shank Length, 1-1/2" Cutoff Length, 3/16" Depth Piece, 300 PPM, Bushing Cutoff

(2) 3/16" National Single Die Tubular Rivet Header; s/n 36165 and 36132, 3/16" Cutoff Diameter, 1" Shank Length, 3/8" Depth of Piece, 225 PPM, Bushing Cutoff, Face of Die Stripper

3/16" National DSSD Cold Header; s/n 31338, 3/16" Cutoff Diameter, 1-1/4" Shank Length, 2" Cutoff Length, 270 PPM, Equipped with Bushing Cutoff

(3) 3/16" National High Speed DSSD Cold Headers; s/n 36556, NA, 36563, 3/16" Cut Off Diameter, 1-1/4" Shank Length, 2" Cutoff Length, 350 PPM, Equipped with Bushing Cutoff, Ace Montor 36,563 - Has PKO

(5) 5/32" Sacma Model SP01 DSSD High Speed Cold Headers; s/n 38AL35, 38AI50, 38AP90, 38W7, 38AP86, 5/32" Cutoff Diameter, 1-3/8" Shank Length, 2" Cutoff Length, 350 PPM, (3) Equipped with Ace Monitors

THREAD ROLLERS

(2) ¼" Roy Model "0" High Speed Flat Die Thread Rollers; s/n 9AL147 and 9AL128, ¼" Thread Diameter, 2-1/2" Thread Length, 3" Blank Length, 400 PPM, 21" Vibratory Bowl

LELAND POWELL - Preliminary Equipment List

3/16" Hartford Model 0-400 High Speed Flat Die Thread Roller; s/n 4-833-58, 3/16" Thread Diameter, 2-1/2" Thread Length, 400 PPM, 21" Vibratory Bowl

MISC. FASTENER EQUIPMENT

Clifton Model 2B200 200 Ton 4-Post Hobbing Press; s/n 0906, 200 Tons, 8" Daylight

5/16" Warren Model WS-1000 High Speed Head Slotter; s/n 1084429, 6-5/16" Blank Diameter, 2" Blank Length, 600 PPM, 24" Vibratory Bowl

3/8" Warren High Speed Shank Slotter; s/n 776430, 3/8" Blank Diameter, 2-1/2" Shank Length, 200 PPM, 24" Vibratory Bowl

WIRE DRAWERS

9/16" RMG Model 910-2554-73 Inline Wire Drawer; s/n 91052679, 9/16" Nominal Wire Diameter, 36" Capstan, 25 HP, 54 FPM, Feed Head, Manual Clamp

3/8" RMG Model 78-1039-87 Inline Wire Drawer; s/n 95063523, 3/8" Nominal Wire Diameter, 28" Capstan, 39 FPM, 10 HP, ACVD

3/8" RMG Model 78-1050-01 Inline Wire Drawer; s/n 910348, 3/8" Nominal Wire Diameter, 50 FPM, 28" Capstan, 10 HP, Manual Roller

3/8" RMG Model 78-2080-21 Inline Wire Drawer; s/n 971430, 3/8" Nominal Wire Diameter, 28" Capstan, 80 FPM, 20 HP

5/16" RMG Model 56-0565-87 Inline Wire Drawer; s/n 00125/61, 5/16" Nominal Wire Diameter, 24" Capstan, 65 FPM, 5 HP, Manual Roller, Reverse Frame

(3) 5/16" RMG Model 56-1065-87 Inline Wire Drawer; s/n 95063521, 96124074 and 9807-4548, 5/16" Nominal Wire Diameter, 65 FPM, 24" Capstan, 10 HP, Manual Roller

5/16" RMG Model 56 Inline Wire Drawer; s/n n/a, 5/16" Nominal Wire Diameter

5/16" Fastener Engineers Model DTVA-0760-24 Inline Wire Drawer; s/n 1977509, 5/16" Nominal Wire Diameter, 24" Capstan, 7 HP, 6-60 FPM

1/4" RMG Model 45 Inline Wire Drawer; s/n n/a, 1/4" Nominal Wire Diameter, 20" Capstan

LELAND POWELL - Preliminary Equipment List

¼" RMG Model 45-10119-68 Inline Wire Drawer; s/n 00055030, ¼" Nominal Wire Diameter, 20" Capstan, 10 HP, 119 FPM

(2) ¼" RMG Model 45-0343-01 Inline Wire Drawer; s/n 210871 and 210872, ¼" Nominal Wire Diameter, 20" Capstan, 3 HP, 43 FPM

¼" RMG Model 45-0550-85 Inline Wire Drawer; s/n 86121666, ¼" Nominal Wire Diameter, 20" Capstan, 5 HP, 50 FPM

3/16" RMG Model 34 Inline Wire Drawer; s/n n/a, 3/16" Nominal Wire Diameter, 20" Capstan

FORKLIFTS AND RELATED

(3) 5,000 Lb. Nissan Uni-Carrier Model MCP1F2A25LV LPG Forklift; 187" Lift 3-Stage Mast, Safety Lights

(4) 5,000 Lb. Nissan Model MCP1F2A25LV LPG Forklift; 187" Lift 3-Stage Mast, Safety Lights

Komatsu Model FG25ST-12 LPG Forklift; 188" Lift 3-Stage Mast

AIR COMPRESSORS AND DRYERS

Quincy Model QSO-500i Cabinet Enclosed Air Compressor; s/n UTY301905 (New 2015)

Gardner Denver Model EBM99K Skid Mount Air Compressor; s/n S304533, 125 PSIG (New 2009)

75-HP Gardner Denver Model EBKOLC Skid Mount Air Compressor; s/n M86008, 115 PSIG

30-HP Leroi Model W30SST Horizontal Tank Air Compressor

Zeks Model 800NCEA500 Air Dryer; s/n WCH1004220

Zeks Model 500NCEA400 Air Dryer; s/n WCH1004317

TOOLROOM MACHINERY

15" x 40" Sharp Model 1540G Gap Bed Engine Lathe

LELAND POWELL - Preliminary Equipment List

2-HP Bridgeport Series 1 Vertical Mill, DRO, Power Table

13" x 40" Goodway Engine Lathe

13" x 40" Jet Engine Lathe

Covel Hand Feed Surface Grinder

Harig Super 618 Hand Feed Surface Grinder

Sunnen MBB-1600 Hone

Hardinge Model TFB-H Precision Lathe

Wardell Model 57T Saw Blade Sharpener

SHOP AND SUPPORT EQUIPMENT

Tennant Model S10 Walk Behind Floor Sweeper

Trinco 24/BP Blast Cabinet

(8) Digital Platform Scales, Most 4' x 4'

Maintenance Area, Saws, Drills, Grinders, Welders, Tools, Parts and Related

Small Machinery, D.E. Grinders, Drill Presses, Saws, Lathes and Related

Shop Equipment, Cabinets, Benches, Tables, Fans, Hoppers, Tubs, Tools, Payoff Tables